

Material Safety Data Sheet

MSDS

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Chemical Name: XPEL Paint Protection Film Sealant

Date of Preparation: 10/1/2008

Section 1 – Chemical Product and Company Identification

Product / Chemical Name: XPEL Paint Protection Film Sealant
Manufacturer's Name: XPEL Technologies Corp.
Address: 13750 San Pedro
Suite 530
San Antonio, TX 78232
General Use: Paint Protection Film Wax/Polish
DOT Hazard Classification Flammable Liquid: 173.115

Emergency Telephone Number: 800-424-9300

Telephone Number for Information: 800-447-9928


Date Prepared: 1/12/2009

Section 2 – Composition / Information on Ingredients

Hazardous Components	OSHA PEL (ppm)	ACGIH TLV (ppm)	CAS#	%
Aliphatic Hydrocarbons	400	400	8052-41-3	20

Section 3 – Hazards Identification

Emergency Overview



Potential Health Effects

Eye Contact:	Eye irritation
Skin Contact:	No irritation or reaction expected.
Inhalation:	N/A
Ingestion:	May cause upset stomach, nausea (Abnormal entry route).

Section 4 – First Aid Measures

Eye Contact: Move individual away from exposure and into fresh air. Flush with plenty of water for at least 15 minutes. Seek medical attention.

Skin Contact: N/A

Inhalation: N/A

Ingestion: Do not induce vomiting. Contact a physician or Poison Control Center.

Section 5 – Fire-Fighting Measures

Flash Point: 108 F

Flammable Limits: N/A

Extinguishing Media: Regular foam, carbon dioxide, and dry chemical.

Autoignition temperature: 420.0 F

Fire-Fighting Equipment: Self-contained breathing apparatus with full face piece

Section 6 – Accidental Release Measures

Small Spill: Absorb spill using vermiculite floor absorbent or other absorbent material.

Large spill: persons not wearing protective equipment should be excluded from area of spill until clean up has been completed. Stop at spill source prevent from spreading. If runoff occurs, notify authorities as required. Floor may be slippery - use care to avoid falls. Remove contaminated clothing and wash before reuse.

RCRA Hazardous Waste Numbers: N/A

Section 7 – Handling and Storage

Storage Requirements: Avoid freezing conditions

Section 8 – Exposure Controls / Personal Protection

Eye Protection: None required under normal conditions.

Skin Protection: None required under normal conditions.

Respiratory Protection: None required under normal conditions.

Ventilation: None required under normal conditions.

Protective Equipment or Clothing: None required under normal conditions.

Section 9 – Physical and Chemical Properties

Appearance and Odor: Creamy blue with sweet odor

Vapor Pressure: <1 mmHg @77 F

Specific Gravity: .804 - .815 @ 60.0 F

pH: 8-9

Melting Point: N/A

Boiling Point: 550 F

Water Solubility: < .01%

Section 10 – Stability and Reactivity

Stability: Stable

Polymerization: Will not occur

Decomposition Products: N/A

Incompatibility (materials to avoid): Avoid contact with: chlorine, hypochlorite, and strong oxidizing agents

Section 11 – Toxicological Information

No Data

Section 12 – Ecological Information

No Data

Section 13 – Disposal Considerations

Waste management information: Dispose of in accordance with all applicable local, state and federal regulations.

Section 14 – Transport Information

Dot information - 49 cfr 172.10

Dot description: (for ground non bulk shipments) not regulated

Container/mode: non bulk

Nos component: na

Rq (reportable quantity) – 49 cfr 172-101 not applicable

Section 15 – Regulatory Information

US Federal Regulations:

Cercla Rq - 40 Cfr 302.4 - None Listed

Sara 302 Components - 40 Cfr 355 Appendix A - None

Sara 313 Components - 40 Cfr 372.65 - None

Section 16 – Other Information

The information herein is given in good faith, but no warranty, express or implied, is made. Consult Chemtrec at 1-800-424-9300 for further information.