

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : XPEL PAINT PROTECTION FILM SEALANT  
Product code : R1326

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

XPEL TECHNOLOGIES, INC.  
618 W. SUNSET  
SAN ANTONIO, TX 78216  
T 210-678-3700

#### 1.4. Emergency telephone number

Emergency number (24 hr) : INFOTRAC 1-352-323-3500 (International)  
: 1-800-535-5053 (North America)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H227 - Combustible liquid  
Precautionary statements (GHS-US) : **P210** - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
**P233** - Keep container tightly closed  
**P240** - Ground/bond container and receiving equipment  
**P241** - Use explosion-proof electrical, lighting, ventilating equipment  
**P242** - Use only non-sparking tools  
**P243** - Take precautionary measures against static discharge  
**P280** - Wear eye protection, face protection, protective clothing, protective gloves  
**P303+P361+P353** - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
**P370+P378** - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish  
**P403+P235** - Store in a well-ventilated place. Keep cool  
**P501** - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	8 - 10	Flam. Liq. 4, H227 Asp. Tox. 1, H304
solvent naphtha(petroleum), medium aliph.	(CAS No) 64742-88-7	8 - 10	STOT RE 1, H372 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove the victim into fresh air. If not breathing give artificial respiration. Get medical advice/attention. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: If skin irritation occurs: Get medical advice/attention. Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Move victim away from exposure and into fresh air. Rinse immediately with plenty of water for 15 minutes. Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
-------------------	--

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry chemical powder. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
-------------	-----------------------

#### 5.3. Advice for firefighters

Firefighting instructions	: Water can be used to keep exposed containers cool, to protect;. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent firefighting water from entering environment.
Protection during firefighting	: Complete protective clothing. Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Absorb spill on vermiculite floor absorbent or other absorbent material.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective goggles.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Absorb spillage to prevent material damage. Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Containers of this material may be hazardous when emptied. All hazard precautions give should be observed.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Emptied containers may retain product residues. Precautions apply to emptied containers. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### XPEL PAINT PROTECTION FILM SEALANT

ACGIH	Not applicable
OSHA	Not applicable
DNEL	DNEL

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

ACGIH	Not applicable
OSHA	Not applicable

##### solvent naphtha(petroleum), medium aliph. (64742-88-7)

ACGIH	Not applicable
OSHA	Not applicable

#### 8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Light Blue Liquid.
- Color : light blue
- Odor : Sweet
- Odor threshold : No data available
- pH : 8 - 9
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No Data
- Freezing point : No data available
- Boiling point : 370 - 550 °F @ 760 mmHg
- Flash point : 108 °F Method TCC
- Auto-ignition temperature : 420 °F

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 1 mmHg @ 77.0 F
Relative vapor density at 20 °C	: No data available
Relative density	: 0.9 - 0.815 @ 60.0 F
Solubility	: Water: < 1
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions. Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
--------------------	---

#### solvent naphtha(petroleum), medium aliph. (64742-88-7)

LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 420; Experimental value)
---------------	---

LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
--------------------	--

Skin corrosion/irritation	: Not classified pH: 8 - 9
Serious eye damage/irritation	: Not classified pH: 8 - 9
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)

##### solvent naphtha(petroleum), medium aliph. (64742-88-7)

LC50 fish 1	2 - 5 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semistatic system; Fresh water; Experimental value)
EC50 Daphnia 1	1.4 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	1 - 3,EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value

#### 12.2. Persistence and degradability

##### XPEL PAINT PROTECTION FILM SEALANT

Persistence and degradability	Not established.
-------------------------------	------------------

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
-------------------------------	--

##### solvent naphtha(petroleum), medium aliph. (64742-88-7)

Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
-------------------------------	--

#### 12.3. Bioaccumulative potential

##### XPEL PAINT PROTECTION FILM SEALANT

Bioaccumulative potential	Not established.
---------------------------	------------------

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

##### solvent naphtha(petroleum), medium aliph. (64742-88-7)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

#### 12.4. Mobility in soil

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Surface tension	0.026 N/m (20 °C)
-----------------	-------------------

#### 12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

# XPEL PAINT PROTECTION FILM SEALANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 14: Transport information

In accordance with DOT  
Not regulated for transport

#### Additional information

Other information : No supplementary information available.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### XPEL PAINT PROTECTION FILM SEALANT

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

#### 15.2.2. National regulations

#### 15.3. US State regulations

### SECTION 16: Other Information

Revision date : 05/27/2015

Other information : None.

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H372	Causes damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product