

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : XPEL PROTECTION FILM CLEANER  
Product code : R1331

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

XPEL TECHNOLOGIES, INC.  
618 W. SUNSET  
SAN ANTONIO, TX 78216  
T 210-678-3700

#### 1.4. Emergency telephone number

Emergency number (24 hr) : INFOTRAC 1-352-323-3500 (International)  
: 1-800-535-5053 (North America)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H315 - Causes skin irritation  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : **P264** - Wash hands, forearms and face, clothing thoroughly after handling  
**P280** - Wear eye protection, protective clothing, protective gloves  
**P302+P352** - If on skin: Wash with plenty of hands, forearms and face  
**P305+P351+P338** - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
**P321** - Specific treatment (see dry extinguishing powder, carbon dioxide (CO<sub>2</sub>), foam on this label)  
**P332+P313** - If skin irritation occurs: Get medical advice/attention  
**P337+P313** - If eye irritation persists: Get medical advice/attention  
**P362** - Take off contaminated clothing and wash before reuse

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	10 - 12	Flam. Liq. 4, H227
butyl glycolether	(CAS No) 111-76-2	2 - 4	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
disodium metasilicate	(CAS No) 6834-92-0	1 - 2	Skin Corr. 1A, H314 STOT SE 3, H335

Full text of H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove the victim into fresh air. If not breathing give artificial respiration. Get medical advice/attention. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: If skin irritation occurs: Get medical advice/attention. Get medical advice/attention. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Move victim away from exposure and into fresh air. Rinse immediately with plenty of water for 15 minutes. Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry chemical powder. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

Firefighting instructions	: Water can be used to keep exposed containers cool, to protect;. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent firefighting water from entering environment.
Protection during firefighting	: Complete protective clothing. Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spill on vermiculite floor absorbent or other absorbent material. Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb spillage to prevent material damage. Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Containers of this material may be hazardous when emptied. All hazard precautions give should be observed. Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.  
Hygiene measures : Wash ... thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/...equipment.  
Storage conditions : Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Emptied containers may retain product residues. Precautions apply to emptied containers. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### XPEL PROTECTION FILM CLEANER

ACGIH	Not applicable	
OSHA	Not applicable	
DNEL	DNEL	≈

#### disodium metasilicate (6834-92-0)

ACGIH	Not applicable
OSHA	Not applicable

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

dipropylene glycol monomethyl ether (34590-94-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
OSHA	Not applicable	

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear Liquid.
Color	: clear
Odor	: Sweet
Odor threshold	: No data available
pH	: 11 - 12
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No Data
Freezing point	: No data available
Boiling point	: 212 °F
Flash point	: > 160 °F Method TCC
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 140 - 130 F
Relative vapor density at 20 °C	: No data available
Relative density	: < 1 H2O=1
Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : • : > 18 g/100ml • : • :
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable under normal conditions. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### disodium metasilicate (6834-92-0)

LD50 dermal rat	> 5000 mg/kg body weight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
-----------------	--

#### butyl glycolether (111-76-2)

LD50 dermal rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	450.000 ppmV/4h
ATE US (vapors)	2.200 mg/l/4h
ATE US (dust, mist)	2.200 mg/l/4h

#### dipropylene glycol monomethyl ether (34590-94-8)

LD50 dermal rat	5135 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg; Rat; Experimental value)
LD50 dermal rat	9500 mg/kg (Rat; Literature study; Equivalent or similar to OECD 402; >19020 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	9500 mg/kg (Rabbit; Literature study)
ATE US (oral)	5135.000 mg/kg body weight
ATE US (dermal)	9500.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.  
pH: 11 - 12

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 11 - 12

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

#### butyl glycolether (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### disodium metasilicate (6834-92-0)

LC50 fish 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; GLP)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)

##### butyl glycoether (111-76-2)

LC50 fish 1	1474 ppm (96 h; Oncorhynchus mykiss)
EC50 Daphnia 1	1550 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	911 mg/l (72 h; Pseudokirchneriella subcapitata)
Threshold limit algae 2	88 mg/l (72 h; Pseudokirchneriella subcapitata)

##### dipropylene glycol monomethyl ether (34590-94-8)

LC50 fish 1	> 10000 mg/l (96 h; Pimephales promelas; GLP)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h; Crangon crangon)
LC50 fish 2	> 150 mg/l (72 h; Pisces)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h; Crangon crangon)
Threshold limit algae 1	969 mg/l (72 h; Selenastrum capricornutum; GLP)
Threshold limit algae 2	> 969 mg/l (72 h; Selenastrum capricornutum; GLP)

#### 12.2. Persistence and degradability

##### XPEL PROTECTION FILM CLEANER

Persistence and degradability	Not established.
-------------------------------	------------------

##### disodium metasilicate (6834-92-0)

Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

##### butyl glycoether (111-76-2)

Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.
-------------------------------	--

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

<b>dipropylene glycol monomethyl ether (34590-94-8)</b>	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available. Photolysis in the air.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
ThOD	2.06 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0 % ThOD

### 12.3. Bioaccumulative potential

<b>XPEL PROTECTION FILM CLEANER</b>	
Bioaccumulative potential	Not established.

<b>disodium metasilicate (6834-92-0)</b>	
Bioaccumulative potential	Bioaccumulation: not applicable.

<b>butyl glycoether (111-76-2)</b>	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>dipropylene glycol monomethyl ether (34590-94-8)</b>	
Log Pow	0.0043 (Experimental value; OECD 102: Melting Point/Melting Range; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>butyl glycoether (111-76-2)</b>	
Surface tension	0.065 N/m (20 °C; 003)

### 12.5. Other adverse effects

Effect on ozone layer :  
Effect on the global warming : No known ecological damage caused by this product.  
Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to ...  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT  
Not regulated for transport

### Additional information

Other information : No supplementary information available.

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

# XPEL PROTECTION FILM CLEANER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | Revision date: 05/27/2015

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### XPEL PROTECTION FILM CLEANER

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

##### disodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

#### 15.2.2. National regulations

#### 15.3. US State regulations

##### butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Revision date 05/27/2015

Other information None.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product