

F I L M C T O C G L S S C H R T C - C S I N G L E C P N E

				CLEAR ANNEALED		TEMPERED / HEAT STRENGTHENED	TINTED ANNEALED	
Product	Visible Light Transmitted	Solar Energy Reflected	Solar Energy Absorbed	Thickness 1/8" - 1/4"		Thickness 1/8" - 3/8"	Thickness 1/8" - 1/4"	
				Up to 40 ft²	40 ft² to 100 ft²	Up to 100 ft²	Up to 40 ft²	40 ft² to 100 ft²
SILVER								
Silver 20 DA	20%	54%	34%	👍	👍	👍	⚠️	⚠️
Silver 30 DA	31%	43%	35%	👍	👍	👍	⚠️	⚠️
Silver 45 DA	45%	29%	36%	👍	👍	👍	👍	👍
BRONZE								
Bronze 20 DA	22%	40%	46%	👍	👍	👍	👍	👍
Bronze 35 DA	35%	30%	45%	👍	👍	👍	👍	👍
NEUTRAL								
Daylight 60 DA	57%	9%	38%	👍	👍	👍	👍	👍
Crystal Clear 70	69%	32%	19%	👍	👍	👍	👍	👍
DUAL REFLECTIVE								
One-Way DA	8%	54%	37%	👍	👍	👍	👍	⚠️
Evening View 15 DA	15%	48%	39%	👍	👍	👍	👍	👍
Evening View 25 DA	26%	28%	44%	👍	👍	👍	👍	👍
Evening View 35 DA	37%	15%	44%	👍	👍	👍	👍	👍
Evening View 45 DA	46%	10%	40%	👍	👍	👍	👍	👍
EXTERIOR								
Exterior Silver 20	18%	59%	26%	👍	👍	👍	👍	👍
ANTI-GRAFFITI								
Anti-Graffiti 4Mil	90%	6%	11%	👍	👍	👍	👍	👍
Anti-Graffiti 6Mil	90%	7%	12%	👍	👍	👍	👍	👍
SAFETY								
Safety Clear 4Mil	90%	6%	11%	👍	👍	👍	👍	👍
Safety Clear 7Mil	90%	7%	12%	👍	👍	👍	👍	👍
Security 8Mil	88%	7%	13%	👍	👍	👍	👍	👍
Security 12Mil	87%	7%	18%	👍	👍	👍	👍	👍
Security 15Mil	86%	9%	14%	👍	👍	👍	👍	👍
SOLAR SAFETY								
Security 8Mil Silver 20	18%	53%	34%	👍	👍	👍	⚠️	⚠️
Security 8Mil Neutral 35	36%	19%	51%	👍	👍	👍	👍	⚠️
DESIGN								
White frost	67%	12%	25%	👍	👍	👍	👍	👍
Black out	0%	7%	92%	👎	👎	👍	👎	👎
White out	0%	37%	62%	👎	👎	👍	👎	👎

CHART LEGEND :



RECOMMENDED



CAUTION RECOMMENDED, PREAPPROVAL REQUIRED



DO NOT USE IN ANY CIRCUMSTANCES

Solar properties are typical values and should not be considered specifications. All solar measurements performed on 3mm glass.